

# Aluminum Round Tubing Chart

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
1/8"	0.13	0.02	0.09	6061-T6	0.0078
	0.13	0.03	0.07	5051-0	0.0099
	0.13	0.04	0.06	5052-0	0.0115
3/16"	0.19	0.02	0.14	3003-H4	0.0136
	0.19	0.03	0.13	2024-T3	0.0171
	0.19	0.03	0.13	3003-0	0.02
1/4"	0.19	0.03	0.13	5052-0	0.02
	0.19	0.03	0.13	6061-T6	0.02
	0.19	0.03	0.13	6061T6HYD	0.02
5/16"	0.19	0.04	0.12	2024-T3	0.02
	0.19	0.04	0.12	5052-0	0.02
	0.19	0.04	0.12	6061-T6	0.02
7/16"	0.19	0.05	0.09	2024-T3	0.0259
	0.19	0.05	0.09	6061-T6	0.0252
	0.25	0.02	0.21	5052-0	0.0168
9/16"	0.25	0.02	0.21	6061-T4	0.0170
	0.25	0.02	0.21	6061-T6	0.0170
	0.25	0.02	0.21	6061T6HYD	0.0170
5/8"	0.25	0.02	0.21	3003-H14	0.0187
	0.25	0.03	0.19	6061-T4	0.0185
	0.25	0.03	0.19	2024-T3	0.0237
11/16"	0.25	0.03	0.19	5052-0	0.0227
	0.25	0.03	0.19	6061-T4	0.0230
	0.25	0.03	0.19	6061-T6	0.0230
13/16"	0.25	0.03	0.19	6061T6HYD	0.0230
	0.25	0.04	0.18	3003-0	0.0260
	0.25	0.04	0.18	2024-T3	0.0286
7/8"	0.25	0.04	0.18	3003-0	0.0208
	0.25	0.04	0.18	3003-H14	0.0281
	0.25	0.04	0.18	3003-H18	0.0281
15/16"	0.25	0.04	0.18	5052-0	0.0275
	0.25	0.04	0.18	6061-0	0.0275
	0.25	0.04	0.18	6061-T6	0.0278
1"	0.25	0.04	0.18	6061T6HYD	0.0278
	0.25	0.05	0.15	2024-T3	0.0375
	0.25	0.05	0.15	5052-0	0.0360
	0.25	0.05	0.15	6061-T6	0.0364

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
1/4"	0.25	0.06	0.13	6061-T6	0.0411
	0.25	0.06	0.13	2024-T3	0.0434
	0.25	0.07	0.12	6061-T6	0.0444
5/16"	0.25	0.08	0.08	2024T3	0.0522
	0.31	0.02	0.27	5052-0	0.0214
	0.31	0.02	0.27	6061-T4	0.0217
3/8"	0.31	0.02	0.27	6061-T6HYD	0.0217
	0.31	0.03	0.26	3003-H18	0.0269
	0.31	0.03	0.26	5052-0	0.0292
7/16"	0.31	0.03	0.26	6061-T6	0.0295
	0.31	0.04	0.24	2024-T3	0.0300
	0.31	0.04	0.24	3003-0	0.0363
11/16"	0.31	0.04	0.24	5052-0	0.0356
	0.31	0.04	0.24	5052-0HYD	0.0356
	0.31	0.04	0.24	6061-T4	0.0359
13/16"	0.31	0.04	0.24	6061-T6	0.0359
	0.31	0.04	0.24	6061T6HYD	0.0359
	0.31	0.05	0.21	2024-T3	0.0493
15/16"	0.31	0.05	0.21	6061-T6	0.0478
	0.31	0.06	0.2	2024-T3	0.0563
	0.31	0.06	0.2	5052-0	0.0541
1"	0.31	0.06	0.19	6061-T6	0.0546
	0.31	0.07	0.18	2024-T3	0.0614
	0.31	0.07	0.16	2024-T3	0.0673
1 1/16"	0.31	0.1	0.12	2024-T3	0.0788
	0.38	0.02	0.34	5052-0	0.0260
	0.38	0.02	0.34	6061-T6	0.0262
1 3/16"	0.38	0.02	0.33	3003-H14	0.0290
	0.38	0.02	0.33	5052-0	0.0284
	0.38	0.02	0.33	6061-T4	0.0287
1 7/16"	0.38	0.03	0.33	3003-H18	0.0327
	0.38	0.03	0.32	2024-0	0.0370
	0.38	0.03	0.32	2024-T3	0.0370
1 15/16"	0.38	0.03	0.32	3003-3	0.0363
	0.38	0.03	0.32	5052-0	0.0355
	0.38	0.03	0.32	6061-T4	0.0359
1 3/4"	0.38	0.03	0.32	6061-T4HYD	0.0359

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
3/8"	0.38	0.03	0.32	6061-T6	0.0359
	0.38	0.03	0.32	6061-T6HYD	0.0453
	0.38	0.04	0.31	2024-T3	0.0444
	0.38	0.04	0.31	3003-0	0.0444
	0.38	0.04	0.31	3003-H14	0.0435
	0.38	0.04	0.31	5052-0	0.0435
	0.38	0.04	0.31	5052-0HYD	0.0440
	0.38	0.04	0.31	6061-0	0.0440
	0.38	0.04	0.31	6061-T4	0.0440
	0.38	0.04	0.31	6061-T4HYD	0.0440
	0.38	0.04	0.31	6061-T6	0.0440
	0.38	0.04	0.31	6061-T6HYD	0.0440
	0.38	0.05	0.28	2024-T3	0.0608
	0.38	0.05	0.28	5052-0	0.0584
	0.38	0.05	0.28	6061-T0	0.0590
	0.38	0.05	0.28	6061-T6	0.0590
	0.38	0.05	0.28	6061-T6HYD	0.0590
	0.38	0.06	0.26	2024T3	0.0700
	0.38	0.06	0.26	3003-H14	0.0686
	0.38	0.06	0.26	5052-0	0.0672
	0.38	0.06	0.26	6061-T0	0.0679
	0.38	0.07	0.25	2024-T3	0.0767
	0.38	0.07	0.25	5052-H34	0.0737
	0.38	0.07	0.25	6061-T6	0.0744
	0.38	0.08	0.21	2024-T3	0.0923
	0.38	0.08	0.21	6061-T6	0.0895
	0.38	0.09	0.19	2024-T3	0.0984
	0.38	0.1	0.19	2024-T3	0.1013
	0.38	0.1	0.19	6061-T6	0.0983
7/16"	0.44	0.04	0.37	2024-T3	0.0537
	0.44	0.04	0.37	3003-0	0.0526
	0.44	0.04	0.37	6061-T6	0.0521
	0.44	0.05	0.34	2024-T3	0.0726
	0.44	0.05	0.34	6061-0	0.0704
	0.44	0.05	0.34	6061-T6	0.0704
	0.44	0.07	0.31	2024-T3	0.0923
	0.44	0.07	0.31	6061-T6	0.0896

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
7/16"	0.44	0.08	0.27	2024-T3	0.1090
	0.44	0.09	0.26	2024-T3	0.1190
	0.44	0.1	0.25	2024T3	0.1241
	0.44	0.12	0.2	6061-T6	0.1453
1/2"	0.5	0.02	0.46	5052-0	0.0351
	0.5	0.02	0.46	6061-T6	0.0355
	0.5	0.02	0.46	2024-T3	0.0400
	0.5	0.02	0.46	3003-0	0.0392
	0.5	0.02	0.46	6061-T6	0.0389
	0.5	0.03	0.44	3003-H14	0.0493
	0.5	0.03	0.44	5052-0	0.0483
	0.5	0.03	0.44	6061-T6	0.0488
	0.5	0.04	0.43	2024-0	0.0620
	0.5	0.04	0.43	3003-H14	0.0607
	0.5	0.04	0.43	5052H32	0.0595
	0.5	0.04	0.43	6061-T6	0.0601
	0.5	0.05	0.4	2024-T3	0.0841
	0.5	0.05	0.4	5052-0	0.0808
	0.5	0.05	0.4	6061-T6	0.0816
	0.5	0.05	0.4	7075-0	0.0841
	0.5	0.06	0.38	2024-T3	0.0976
	0.5	0.06	0.38	6061-T6	0.0947
	0.5	0.07	0.37	2024T3	0.1077
	0.5	0.07	0.37	5052-0	0.1034
	0.5	0.07	0.37	6061-T6	0.1045
	0.5	0.08	0.33	2024-T3	0.1318
	0.5	0.08	0.33	6061-T6	0.1279
	0.5	0.1	0.31	2024-T3	0.1465
	0.5	0.1	0.31	6061-T6	0.1421
	0.5	0.12	0.26	2024-T3	0.1736
	0.5	0.12	0.26	6061-T6	0.1685
	0.5	0.13	0.25	6061-T6	0.1732
9/16"	0.56	0.02	0.53	6061-T4	0.0323
	0.56	0.04	0.49	2024-T3	0.0704
	0.56	0.05	0.46	2024-T3	0.0959
	0.56	0.13	0.31	2024-T3	0.2084
5/8"	0.63	0.02	0.59	5052-0	0.0443

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
5/8"	0.63	0.03	0.57	2024T3	0.0636
	0.63	0.03	0.57	3003-0	0.0624
	0.63	0.03	0.57	5052-0	0.0611
	0.63	0.03	0.57	6061-T6	0.0618
	0.63	0.04	0.56	2024T3	0.0786
	0.63	0.04	0.56	3003-H14	0.0771
	0.63	0.04	0.56	5052-0	0.0755
	0.63	0.04	0.56	6061-T6	0.0763
	0.63	0.04	0.54	6061-T6	0.0905
	0.63	0.05	0.53	2024-T3	0.1075
	0.63	0.05	0.53	3003-H32	0.1053
	0.63	0.05	0.53	5052-0	0.1032
	0.63	0.05	0.53	6061-T6	0.1043
	0.63	0.06	0.51	2024-T3	0.1252
	0.63	0.06	0.51	6061-T6	0.1215
	0.63	0.07	0.5	2024-T3	0.1386
	0.63	0.07	0.5	5052-0	0.1331
	0.63	0.07	0.5	6061-T6	0.1345
	0.63	0.08	0.46	2024-T3	0.1713
	0.63	0.08	0.46	6061-T6	0.1662
	0.63	0.1	0.44	2024-T3	0.1917
	0.63	0.13	0.38	6061-T6	0.2309
	0.63	0.16	0.31	6061-T6	0.2703
3/4"	0.75	0.02	0.71	6061-T4	0.0539
	0.75	0.03	0.69	2024-T3	0.0770
	0.75	0.03	0.69	3003-H14	0.0755
	0.75	0.03	0.69	5052-0	0.0739
	0.75	0.03	0.69	6061-T6	0.0747
	0.75	0.04	0.68	2024-T3	0.0953
	0.75	0.04	0.68	3003-H14	0.0934
	0.75	0.04	0.68	5052-0	0.0915
	0.75	0.04	0.68	6061-T6	0.0925
	0.75	0.04	0.67	7975-0	0.1132
	0.75	0.05	0.65	2024-T3	0.1308
	0.75	0.05	0.65	3003-0	0.1282
	0.75	0.05	0.65	5052-0	0.1256
	0.75	0.05	0.65	6061-T6	0.1269

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
7/8"	0.75	0.06	0.63	2024-T6	0.1528
	0.75	0.06	0.63	6061-T6	0.1483
	0.75	0.07	0.62	2024-T3	0.1695
	0.75	0.07	0.62	3003-H14	0.1661
	0.75	0.07	0.62	5052-0	0.1629
	0.75	0.07	0.62	6061-T6	0.1645
	0.75	0.08	0.58	2024-T3	0.2108
	0.75	0.08	0.58	6061-T6	0.2045
	0.75	0.08	0.58	7075-T6	0.2108
	0.75	0.1	0.55	2024-T3	0.2369
	0.75	0.1	0.51	6061-T6	0.2401
	0.75	0.12	0.51	2024-T3	0.2879
	0.75	0.12	0.5	6061-T6	0.2793
	0.75	0.13	0.44	6061-T6	0.2886
	0.75	0.16	0.41	6061-T6	0.3424
	0.75	0.17	0.37	6061-T6	0.3643
	0.75	0.19	0.37	2024-T3	0.0423
7/8"	0.88	0.03	0.82	2024-T3	0.0903
	0.88	0.03	0.82	6061-T6	0.0876
	0.88	0.04	0.81	2024-T3	0.1119
	0.88	0.04	0.81	5052-0	0.1075
	0.88	0.04	0.81	6061-T6	0.1086
	0.88	0.05	0.78	2024-T3	0.1541
	0.88	0.05	0.78	6061-T6	0.1495
	0.88	0.06	0.76	2024-T3	1804.0000
	0.88	0.06	0.76	6061-T6	0.1751
	0.88	0.07	0.75	2024-T3	0.2005
	0.88	0.07	0.75	3003-H14	0.1965
	0.88	0.07	0.75	6061-T6	0.1945
	0.88	0.08	0.71	6061-T6	0.2429
	0.88	0.1	0.69	2024-T3	0.2822
	0.88	0.1	0.69	6061-T6	0.2738
	0.88	0.12	0.64	2024-T3	0.3459
	0.88	0.12	0.64	5086-H32	0.3279
	0.88	0.12	0.64	6061-T6	0.3347
	0.88	0.19	0.5	2024-T3	0.4918
1"	1	0.02	0.96	6061-T4	0.0724

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
1"	1	0.02	0.96	5052-0	0.0787
	1	0.02	0.96	6061-T4	0.0795
	1	0.03	0.94	5052-0	0.0995
	1	0.03	0.94	6061-T6	0.1005
	1	0.04	0.93	2024-T3	0.1286
	1	0.04	0.93	3003-H14	0.1261
	1	0.04	0.93	5052-0	0.1235
	1	0.04	0.93	6061-T6	0.1248
	1	0.04	0.93	7075-0	0.1286
	1	0.04	0.92	6061-T6	0.1487
	1	0.05	0.9	1100-0	0.1722
	1	0.05	0.9	2024-T3	0.1774
	1	0.05	0.9	5052-0	0.1704
	1	0.05	0.9	6061-T6	0.1722
	1	0.06	0.88	2024-T3	0.2080
	1	0.06	0.88	6061-T6	0.2019
	1	0.07	0.87	2024-T3	0.2314
	1	0.07	0.87	3003-H14	0.2268
	1	0.07	0.87	5052-0	0.2222
	1	0.07	0.87	6061-T6	0.2245
	1	0.08	0.83	1100-0	0.2812
	1	0.08	0.83	2024-T3	0.2898
	1	0.08	0.83	6061-T6	0.2812
	1	0.1	0.81	2024-T3	0.3274
	1	0.1	0.81	6061-T6	0.3176
	1	0.12	0.76	2024-T3	0.4021
	1	0.12	0.76	6061-T6	0.3901
	1	0.13	0.75	6061-T6	0.4041
	1	0.16	0.69	2024-T3	0.5013
	1	0.19	0.62	2024-T3	0.5813
	1	0.19	0.62	6061-T6	0.5640
	1	0.25	0.5	6061-T6	0.6927
	1	0.25	0.5	7075-T6	0.7139
<b>1 1/8"</b>	1.13	0.02	1.09	5052-0	0.0800
	1.13	0.04	1.06	2024-T3	0.1438
	1.13	0.04	1.06	6061-T6	0.1409
	1.13	0.05	1.03	2024-T3	0.2008

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>1 1/8"</b>	1.13	0.05	1.03	6061-T6	0.1948
	1.13	0.06	1.01	2024-T3	0.2356
	1.13	0.06	1.01	6061-T6	0.2286
	1.13	0.07	1	2024-T3	0.2626
	1.13	0.07	1	6061-T4	0.2546
	1.13	0.07	1	6061-T6	0.2546
	1.13	0.08	0.96	2024-T3	0.3293
	1.13	0.08	0.96	6061-T6	0.3195
	1.13	0.1	0.94	2024-T3	0.3725
	1.13	0.1	0.94	6061-T6	0.3615
	1.13	0.11	0.91	2024-T3	0.4217
	1.13	0.12	0.89	2024-T3	0.4592
	1.13	0.13	0.88	6061-T6	0.4618
	1.13	0.13	0.88	7075-T6	0.4760
	1.13	0.16	0.81	7075-T7	0.5756
	1.13	0.19	0.75	2024-T3	0.6707
	1.13	0.25	0.63	2024-T3	0.8329
	1.13	0.25	0.63	6061-T6	0.8082
<b>1 1/4"</b>	1.25	0.02	1.21	6061-T4	0.0998
	1.25	0.03	1.19	5052-0	0.1251
	1.25	0.03	1.19	6061-T4	0.1264
	1.25	0.03	1.19	6061-T6	0.1264
	1.25	0.03	1.19		0.1264
	1.25	0.04	1.18	2024-T3	0.1619
	1.25	0.04	1.18	3003-H32	0.1587
	1.25	0.04	1.18	5052-0	0.1555
	1.25	0.04	1.18		0.1571
	1.25	0.04	1.18		0.1571
	1.25	0.04	1.18	6061-T6	0.1571
	1.25	0.04	1.18		0.1571
	1.25	0.05	1.15	2024-T3	0.2241
	1.25	0.05	1.15	3003-H14	0.2196
	1.25	0.05	1.15	5052-0	0.2152
	1.25	0.05	1.15		0.2174
	1.25	0.05	1.15		0.2174
	1.25	0.05	1.15	6061-T6	0.2174
	1.25	0.06	1.13	2024-T3	0.2632

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>1 1/4"</b>	1.25	0.06	1.13	6061-T6	0.2554
	1.25	0.07	1.12	2024-T3	0.2933
	1.25	0.07	1.12	3003-H14	0.2875
	1.25	0.07	1.12	5052-0	0.2817
	1.25	0.07	1.12		0.2845
	1.25	0.07	1.12	6061-T6	0.2845
	1.25	0.07	1.12		0.2817
	1.25	0.07	1.12	7075-T7	0.2933
	1.25	0.08	1.08	2024-T3	0.3688
	1.25	0.08	1.08		0.3579
	1.25	0.08	1.08	6061-T6	0.3579
	1.25	0.1	1.06	2024-T3	0.4178
	1.25	0.1	1.06	6061-T6	0.4054
	1.25	0.12	1.01	2024-T3	0.5163
	1.25	0.12	1.01	6061-T6	0.5010
	1.25	0.12	1.01	7075-T7	0.5163
	1.25	0.13	1	6061-T6	0.5196
	1.25	0.16	0.94	2024-T3	0.65
	1.25	0.16	0.94	7075-T0	0.65
	1.25	0.19	0.87	2024-T3	0.76
	1.25	0.19	0.87		0.74
	1.25	0.19	0.87	6061-T6	0.74
	1.25	0.25	0.75	2024-T3	0.95
	1.25	0.25	0.75	5086-H32	0.9
	1.25	0.25	0.75	6061-T6	0.92
	1.25	0.25	0.75		0.92
	1.25	0.31	0.62	6061-T6	1.08
<b>1 3/8"</b>	1.38	0.02	1.34	6061-T6	0.1
	1.38	0.03	1.32	2024-T3	0.14
	1.38	0.04	1.31	2024-T3	0.1786
	1.38	0.04	1.31	6061-T4	0.1733
	1.38	0.04	1.31	6061-T6	0.1733
	1.38	0.05	1.28	2024-T3	0.2474
	1.38	0.05	1.28	6061-T6	0.2400
	1.38	0.06	1.26	6061-T6	0.2822
	1.38	0.06	1.26		0.2822
	1.38	0.06	1.25	6063-T6	0.2877

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>1 3/8"</b>	1.38	0.07	1.25	6061-T6	0.3146
	1.38	0.08	1.21	6061-T6	0.3962
	1.38	0.08	1.21	2024-T3	0.4083
	1.38	0.13	1.13	2024-T3	0.5950
	1.38	0.13	1.13	5052-0	0.5714
	1.38	0.13	1.13	6061-T6	0.5773
	1.38	0.13	1.13		0.5773
	1.38	0.13	1.13	7075-T6	0.5950
	1.38	0.19	1	2024-T3	0.8497
	1.38	0.19	1	7075-T6	0.8497
	1.38	0.25	0.88	2024-T3	1.0710
	1.38	0.25	0.88	6061-T6	1.0390
	1.38	0.25	0.88		1.0390
	1.38	0.25	0.88	7075-T6	1.0710
	1.38	0.38	0.88	6061-T6	1.39
<b>1 1/2"</b>	1.5	0.02	1.46	6061-T6	0.1094
	1.5	0.03	1.44	5052-0	0.1507
	1.5	0.03	1.44	6061-0	0.1523
	1.5	0.03	1.44	6061-T4	0.1523
	1.5	0.03	1.44	6061-T6	0.1523
	1.5	0.03	1.44	6061-T6 HYD	0.1523
	1.5	0.04	1.43	2024-T3	0.1952
	1.5	0.04	1.43	5052-0	0.1875
	1.5	0.04	1.43	6061-0	0.1894
	1.5	0.04	1.43	6061-T4	0.1894
	1.5	0.04	1.43	6061-T6	0.1894
	1.5	0.04	1.43	6061-T6 HYD	0.1894
	1.5	0.05	1.4	2024-0	0.2707
	1.5	0.05	1.4	2024-T3	0.2707
	1.5	0.05	1.4	3003-H14	0.2653
	1.5	0.05	1.4	5052-0	0.2600
	1.5	0.05	1.4	6061-0	0.2627
	1.5	0.05	1.4	6061-T4	0.2627
	1.5	0.05	1.4	6061-T6	0.2627
	1.5	0.06	1.38	6061-T4	0.3090
	1.5	0.06	1.38	6061-T6	0.3090
	1.5	0.06	1.38	6063-T6	0.3058

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>1 1/2"</b>	1.5	0.06	1.38	6063-T6	0.3260
	1.5	0.07	1.37	2024-T3	0.3552
	1.5	0.07	1.37	5052-0	0.3411
	1.5	0.07	1.37	6061-T4	0.3446
	1.5	0.07	1.37	6061-T6	0.3446
	1.5	0.07	1.37	6063-T832 FG	0.3411
	1.5	0.08	1.33	2024-T3	0.4478
	1.5	0.08	1.33	6061-0	0.4345
	1.5	0.08	1.33	6061-T6	0.43
	1.5	0.08	1.33	6063-T832	0.43
	1.5	0.1	1.31	2024-T3	0.51
	1.5	0.1	1.31	6061-T6	0.49
	1.5	0.12	1.26	2024-T3	0.63
	1.5	0.13	1.25	6061-T6	0.64
	1.5	0.13	1.37	6061-T6511	0.64
	1.5	0.16	1.37	2024-T3	0.8
	1.5	0.19	1.33	2024-T3	0.94
	1.5	0.19	1.33	6061-T6	0.91
	1.5	0.19	1.33	6061-T6511	0.91
	1.5	0.25	1.33	2024-T3	1.3
	1.5	0.25	1.31	6061-T6	1.1550
	1.5	0.25	1.31	6061-T6511	1.1550
	1.5	0.38	1.26	2024-T3511	1.6060
	1.5	0.38	1.25	6061-T6	1.5590
<b>1 5/8"</b>	1.63	0.04	1.56	2024-T3	0.21
	1.63	0.04	1.56	6061-T6	0.21
	1.63	0.05	1.53	2024-T3	0.29
	1.63	0.05	1.53	6061-T6	0.2853
	1.63	0.06	1.51	6061-T6	0.3358
	1.63	0.07	1.5	2024-T3	0.3861
	1.63	0.13	1.38	6061-T6	0.6927
	1.63	0.19	1.25	2024-T3	1.0290
	1.63	0.19	1.25	6061-T6	0.9981
	1.63	0.25	1.13	2024-T3	1.3090
	1.63	0.31	1	6061-T6511	1.5170
<b>1 3/4"</b>	1.75	0.03	1.69	6061-T4	0.1781
	1.75	0.03	1.69	6061-T6	0.1781

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>1 3/4"</b>	1.75	0.04	1.37	2024-T3	0.2287
	1.75	0.04	1.37	3003-0	0.2240
	1.75	0.04	1.25	6061-0	0.2218
	1.75	0.04	1.25	6061-T4	0.2218
	1.75	0.04	1.25	6061-T6	0.2218
	1.75	0.05	1	2024-T3	0.3174
	1.75	0.05	1	5052-0	0.3048
	1.75	0.05	1.68	6061-0	0.3079
	1.75	0.05	1.68	6061-T6	0.3079
	1.75	0.06	1.65	2024-T3	0.3737
	1.75	0.06	1.65	6061-0	0.3626
	1.75	0.06	1.63	6061-T6	0.3626
	1.75	0.07	1.62	2024-T3	0.4170
	1.75	0.07	1.5	3003-H14	0.4088
	1.75	0.07	1.37	6061-T6	0.4046
	1.75	0.08	1.37	2024-T3	0.5268
	1.75	0.08	1.25	6061-T6	0.5112
	1.75	0.1	1.12	2024-T3	0.5987
	1.75	0.1	1.69	5086-H32	0.5690
	1.75	0.12	1.69	2024-T3	0.7448
	1.75	0.13	1.68	6061-T6	0.7505
	1.75	0.13	1.68	6061-T6511	0.7505
	1.75	0.16	1.68	2024-T3	0.9468
	1.75	0.19	1.68	6061-T6	1.0850
	1.75	0.25	1.68	2024-T3	1.4280
	1.75	0.25	1.65	6061-T6	1.3850
	1.75	0.25	1.65	6061-T6511	1.3850
	1.75	0.38	1.65	2024-T3511	1.9630
	1.75	0.38	1.65	6061-T6511	1.9050
<b>1 7/8"</b>	1.88	0.05	1.78	2024-T3	0.3407
	1.88	0.05	1.78	6061-T6	0.3306
	1.88	0.06	1.76	6061-T6	0.3893
	1.88	0.07	1.75	2024-T3	0.4480
	1.88	0.08	1.71	6061-T6	0.5495
	1.88	0.12	1.64	6061-T6	0.7781
	1.88	0.25	1.38	6061-T6	1.5010
	1.88	0.25	1.38	6061-T6511	1.5010

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>1 7/8"</b>	1.88	0.38	1.13	6061-T6511	2.08
<b>2"</b>	2	0.02	1.96	6061-T4	0.1608
	2	0.03	1.94	5052-0	0.2020
	2	0.03	1.94	6061-T4	0.2040
	2	0.03	1.94	6061-T6	0.2040
	2	0.04	1.93	5052-0	0.2515
	2	0.04	1.93	6061-0	0.2541
	2	0.04	1.93	6061-T4	0.2541
	2	0.04	1.93	6061-T6	0.2541
	2	0.04	1.93	6061-T6 HYD	0.2541
	2	0.04	1.92	5052-0	0.3008
	2	0.04	1.92	6061-0	0.3038
	2	0.04	1.92	6061-T4	0.3038
	2	0.04	1.92	6061-T6	0.3038
	2	0.05	1.9	2024-T3	0.3640
	2	0.05	1.9	3003-H14	0.3567
	2	0.05	1.9	5052-0	0.3496
	2	0.05	1.9	6061-0	0.3532
	2	0.05	1.9	6061-T4	0.3532
	2	0.05	1.9	6061-T6	0.3532
	2	0.06	1.88	6061-T6	0.4161
	2	0.06	1.88	6063-T6	0.4119
	2	0.06	1.88	6063-T6	0.4394
	2	0.06	1.88	6063-T6	0.4394
	2	0.07	1.87	2024-T3	0.4789
	2	0.07	1.87	5052-0	0.4600
	2	0.07	1.87	6061-0	0.4647
	2	0.07	1.87	6061-T6	0.4647
	2	0.08	1.83	2024-0	0.6058
	2	0.08	1.83	6061-T6	0.5879
	2	0.08	1.83	6063-T832	0.5819
	2	0.1	1.81	2024-T3	0.6891
	2	0.1	1.81	6063-T832	0.6618
	2	0.12	1.76	2024-T3	0.8590
	2	0.13	1.75	5086-T32	0.8483
	2	0.13	1.75	6061-T6	0.8659
	2	0.13	1.75	6061-T6511	0.8659

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>2"</b>	2	0.16	1.69	2024-T3	1.0950
	2	0.19	1.62	2024-T3	1.2970
	2	0.19	1.62	6061-T6	1.2590
	2	0.19	1.62	6061-T6511	1.2590
	2	0.25	1.5	2024-T3	1.6660
	2	0.25	1.5	6061-T6511	1.6160
	2	0.25	1.5	6061-T6	1.6160
	2	0.25	1.5	6063-T6	1.6000
	2	0.31	1.37	2024-T3	2.0100
	2	0.38	1.25	6061-T6511	2.2510
	2	0.5	1	2011-T3	2.8840
	2	0.5	1	6061-T6511	2.7710
<b>2 1/8"</b>	2.13	0.04	2.06	6061-T6	0.2703
	2.13	0.1	1.94	2024-T3	0.7343
	2.13	0.1	1.94	6061-T6	0.7125
	2.13	0.16	1.81	2024-T3	1.1700
	2.13	0.22	1.68	6061-T6511	1.5670
<b>2 1/4"</b>	2.25	0.04	2.18	5052-0	0.2836
	2.25	0.04	2.18	6061-0	0.2864
	2.25	0.04	2.18	6061-T4	0.2864
	2.25	0.04	2.18	6061-T4 HYD	0.2864
	2.25	0.05	2.15	6061-0	0.4
	2.25	0.05	2.15	6061-T4	0.4
	2.25	0.05	2.15	6061-T6	0.4
	2.25	0.05	2.15	6063-T6	0.39
	2.25	0.06	2.13	2024-T3	0.4841
	2.25	0.07	2.12	3003-0	0.5300
	2.25	0.07	2.12	6061-T6	0.5247
	2.25	0.07	2.12	6063-T6	0.5194
	2.25	0.08	2.08	6061-T6	0.6645
	2.25	0.1	2.06	2024-T3	0.7795
	2.25	0.1	2.06	6061-T6	0.7564
	2.25	0.13	2	6061-T6	0.9814
	2.25	0.13	2	6061-T6511	0.9814
	2.25	0.16	1.94	2024-T3	1.2440
	2.25	0.19	1.87	6061-T6	1.4320
	2.25	0.19	1.87	6061-T6511	1.4320

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>2 1/4"</b>	2.25	0.25	1.75	2011-T3	1.9230
	2.25	0.25	1.75	2024-T3	1.9040
	2.25	0.25	1.75	6061-T6	1.8470
	2.25	0.25	1.75	6061-T6511	1.8470
	2.25	0.25	1.75	6061-T6	1.8470
	2.25	0.31	1.62	6061-T6511	2.2400
	2.25	0.38	1.5	6061-T6	2.5980
	2.25	0.38	1.5	6061-T6511	2.5980
	2.25	0.5	1.25	2011-T3	3.3650
	2.25	0.5	1.25	6061-T6511	3.2330
<b>2 3/8"</b>	2.38	0.11	2.16	Pipe	0.9125
	2.38	0.19	2	6061-T6	1.5190
	2.38	0.25	1.88	6061-T6	1.9630
	2.38	0.25	1.88	6061-T6511	1.9630
	2.38	0.37	1.64	7075-T6	2.8250
	2.38	0.38	1.63	6061-T6511	2.7710
<b>2 1/2"</b>	2.5	0.02	2.46	6061-T4	0.2014
	2.5	0.03	2.44	5052-0	0.2532
	2.5	0.03	2.44	6061-T4	0.2557
	2.5	0.03	2.44	6061-T6	0.2557
	2.5	0.04	2.43	5052-0	0.3155
	2.5	0.04	2.43	6061-0	0.3187
	2.5	0.04	2.43	6061-T4	0.3187
	2.5	0.04	2.43	6061-T6	0.3187
	2.5	0.05	2.4	2024-T3	0.4573
	2.5	0.05	2.4	5052-0	0.4393
	2.5	0.05	2.4	6061-0	0.4437
	2.5	0.05	2.4	6061-T4	0.4437
	2.5	0.05	2.4	6061-T6	0.4437
	2.5	0.06	2.38	6061-0	0.5233
	2.5	0.06	2.38	6061-T4	0.5233
	2.5	0.07	2.37	2024-T3	0.6027
	2.5	0.07	2.37	6061-0	0.5847
	2.5	0.07	2.37	6061-T4	0.5847
	2.5	0.07	2.37	6061-T6	0.5847
	2.5	0.07	2.37	6063-T6	0.5788
	2.5	0.08	2.33	2024-T3	0.7639

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>2 1/2"</b>	2.5	0.08	2.33	6061-0	0.7412
	2.5	0.08	2.33	6061-T6	0.7412
	2.5	0.12	2.26	2024-T3	1.0870
	2.5	0.13	2.25	5086-H32	1.0860
	2.5	0.13	2.25	6061-T6	1.0970
	2.5	0.19	2.12	6061-T6	1.6060
	2.5	0.19	2.12	6061-T6511	1.6060
	2.5	0.25	2	2024-T3	2.1420
	2.5	0.25	2	2024-T3511	2.1420
	2.5	0.25	2	6061-T6	2.0780
	2.5	0.25	2	6061-T6511	2.0780
	2.5	0.31	1.87	6061-T6511	2.5290
	2.5	0.38	1.75	6061-T6	2.9440
	2.5	0.38	1.75	6061-T6511	2.9440
	2.5	0.5	1.5	2011-T3	3.8450
	2.5	0.5	1.5	2024-T3511	3.8080
	2.5	0.5	1.5	6061-T6511	3.6950
	2.5	0.75	1	6061-T6511	4.8490
<b>2 5/8"</b>	2.63	0.07	2.5	6061-T	0.6148
<b>2 3/4"</b>	2.75	0.04	2.68	5052-0	0.3475
	2.75	0.04	2.68	6061-T6	0.3511
	2.75	0.05	2.65	6061-0	0.4890
	2.75	0.05	2.65	6061-T6	0.4890
	2.75	0.07	2.62	2024-T3	0.6645
	2.75	0.07	2.62	3003-0	0.6514
	2.75	0.07	2.62	6061-T6	0.6448
	2.75	0.13	2.5	6061-T6511	1.2120
	2.75	0.25	2.25	2011-T3	2.4030
	2.75	0.25	2.25	2024-T3	2.3800
	2.75	0.25	2.25	6061-T6511	2.3090
	2.75	0.31	2.13	2024-T3511	2.8960
	2.75	0.38	2	2024-T3511	3.3910
	2.75	0.38	2	6061-T6511	3.2900
	2.75	0.5	1.75	2024-T3511	4.2840
	2.75	0.5	1.75	6061-T6511	4.1560
	2.75	0.75	1.25	6061-T6511	5.5420

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
2 7/8"	2.88	0.08	2.71	Pipe	0.8562
	2.88	0.12	2.64	Pipe	1.2210
	2.88	0.2	2.47	Pipe	2.0100
	2.88	0.28	2.32	Pipe	2.6500
	2.88	0.38	2.13	2024-T3511	3.5700
3"	3	0.02	2.96	6061-T4	0.2421
	3	0.02	2.96	6061-T6	0.24
	3	0.03	2.94	5052-0	0.3
	3	0.03	2.94	6061-T4	0.31
	3	0.03	2.94	6061-T6	0.3074
	3	0.04	2.93	5052-0	0.3795
	3	0.04	2.93	6061-0	0.3834
	3	0.04	2.93	6061-T4	0.3834
	3	0.04	2.93	6061-T6	0.3834
	3	0.04	2.92	6061-0	0.4590
	3	0.05	2.9	5052-0	0.5289
	3	0.05	2.9	6061-0	0.5342
	3	0.05	2.9	6061-T6	0.5342
	3	0.07	2.87	5052-0	0.6978
3 1/4"	3	0.07	2.87	5052-0	0.7048
	3	0.07	2.87	6061-T6	0.7048
	3	0.07	2.87	6063-T6	0.6976
	3	0.08	2.83	5052-0	0.8856
	3	0.08	2.83	6061-T6	0.8945
	3	0.1	2.81	6061-T6	1.0200
	3	0.11	2.78	3003-H16	1.1760
	3	0.12	2.76	2024-T3	1.3160
	3	0.13	2.75	6061-T6	1.3280
	3	0.13	2.75	6061-T6511	1.3280
	3	0.19	2.62	2024-T3	2.0130
	3	0.19	2.62	6061-T6511	1.9530
	3	0.25	2.5	6061-T6511	2.5400
	3	0.25	2.5	6063-T832	2.5140
3 1/2"	3	0.31	2.37	6061-T6511	3.1070
	3	0.38	2.25	2024-T3511	3.7480
	3	0.38	2.25	6061-T6511	3.6370
	3	0.5	2	2024-T3511	4.7600

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
3"	3	0.5	2	6061-T6511	4.6180
	3	0.5	2	6061-T6	4.1680
	3	0.5	2	7075-T6	4.7600
	3	0.75	1.5	6061-T6511	6.2350
	3	1	1	6061-T6511	7.3890
3 1/4"	3.25	0.07	3.12	6061-T6	0.7649
	3.25	0.07	3.12	6063-T6	0.7571
	3.25	0.13	3	2024-T3	1.4870
	3.25	0.13	3	6061-T6	1.4430
	3.25	0.25	2.75	6061-T6511	2.7710
	3.25	0.38	2.5	6061-T6511	3.9830
	3.25	0.5	2.25	2024-t3511	5.2360
	3.25	0.5	2.25	6061-T6511	5.0800
	3.25	0.75	1.75	6061-T6511	6.93
	3.5	0.022	3.46	6061-0	0.2827
	3.5	0.022	3.46	6061-T4	0.2827
	3.5	0.028	3.44	5052-0	0.3555
	3.5	0.028	3.44	6061-T4	0.3592
	3.5	0.035	3.43	6061-0	0.4481
3 1/2"	3.5	0.035	3.43	6061-T4	0.4481
	3.5	0.035	3.43	6061-T6	0.4481
	3.5	0.042	3.42	6061-T4	0.5366
	3.5	0.049	3.4	6061-T6	0.6247
	3.5	0.049	3.4	6061-T6	0.6247
	3.5	0.065	3.37	6061-T6	0.8249
	3.5	0.065	3.37	6061-T6511	0.8249
	3.5	0.083	3.33	Pipe	1.0480
	3.5	0.095	3.31	6061-T4	1.1950
	3.5	0.120	3.26	Pipe	1.4980
	3.5	0.125	3.25	6061-T6	1.5590
	3.5	0.125	3.25	6061-T6511	1.5590
	3.5	0.188	3.12	6061-T6511	2.3010
	3.5	0.189	3.12	6063-0	2.2880
	3.5	0.216	3.07	Pipe	2.6210
3.5	0.250	3	6061-T6511	3.0020	
	0.375	2.75	2024-T511	4.4620	

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>3 1/2"</b>	3.5	0.375	2.75	6061-T6511	4.3300
	3.5	0.500	2.5	2024-T3511	5.7110
	3.5	0.500	2.5	6061-T6511	5.5420
	3.5	0.750	2	2024-T3511	7.8530
	3.5	0.750	2	6061-T6511	7.6200
	3.5	1.000	1.5	6061-T6511	9.2370
<b>3 3/4"</b>	3.75	0.250	3.25	6061-T6511	3.2330
	3.75	0.313	3.12	2024-T6511	4.0960
	3.75	0.500	2.75	2024-T3511	6.1880
	3.75	0.500	2.75	6061-T6511	6.0040
	3.75	0.563	2.62	6061-T6511	6.6290
	3.75	0.625	2.5	6061-T6511	7.2160
	3.75	0.750	2.25	6061-T6511	8.3130
	3.75	1.000	1.75	6061-T6511	10.1600
	3.75	1.125	1.5	6061-T6511	10.9100
<b>4"</b>	4	0.028	3.94	6061-T4	0.4109
	4	0.042	3.92	6061-0	0.5127
	4	0.042	3.92	6061-T4	0.5127
	4	0.042	3.92	6061-T6	0.5127
	4	0.042	3.92	6061-T6	0.6142
	4	0.049	3.9	5052-0	0.7081
	4	0.049	3.9	6061-0	0.7153
	4	0.049	3.9	6061-T4	0.7153
	4	0.049	3.9	6061-T6	0.7153
	4	0.065	3.87	5052-0	0.9355
	4	0.065	3.87	6061-0	0.9450
	4	0.065	3.87	6061-T4	0.9450
	4	0.065	3.87	6061-T6	0.9450
	4	0.065	3.87	6063-T6	0.9353
	4	0.083	3.83	6063-T1	1.1890
	4	0.083	3.83	6063-T6	1.1890
	4	0.125	3.75	6061-T6	1.7900
	4	0.125	3.75	6061-T6511	1.7900
	4	0.188	3.62	2014-T	2.7290
	4	0.188	3.62	6061-T6511	2.6480
	4	0.188	3.62	6061-T6511	2.6480
	4	0.225	3.55	7075-T6	3.2340

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>4"</b>	4	0.225	3.55	7075-T6511	3.2340
	4	0.250	3.5	2024-T3511	3.5700
	4	0.250	3.5	6061-T6511	3.4640
	4	0.318	3.36	Pipe	4.3260
	4	0.375	3.25	6061-T6511	5.0220
	4	0.438	3.12	6061-T4	5.7640
	4	0.500	3	2024-T3511	6.6630
	4	0.500	3	6061-T6511	6.4650
	4	0.625	2.75	6061-T6511	7.7930
	4	0.688	2.62	5086-H111	8.2470
	4	0.750	2.5	6061-T6511	9.0060
	4	0.750	2.5	7075-T6511	9.2810
	4	1.000	2	6061-T6511	11.0800
<b>4 1/8"</b>	4.13	0.375	3.38	6061-T6511	5.1950
<b>4 1/4"</b>	4.25	0.125	4	6061-T6511	1.9050
	4.25	0.125	4	6061-T6511	1.9050
	4.25	0.250	3.75	2024-T3511	3.8080
	4.25	0.250	3.75	6061-T6511	3.6950
	4.25	0.375	3.5	6061-T6511	5.3690
	4.25	0.500	3.25	6061-T6511	6.9270
	4.25	0.750	2.75	6061-T6511	9.6980
	4.25	0.750	2.75	7075-T6511	9.9950
	4.25	1.000	2.25	6061-T6511	12.0100
<b>4 3/8"</b>	4.38	0.080	4.22	6061-0	1.2690
<b>4 1/2"</b>	4.5	0.028	4.44	6061-T4	0.4626
	4.5	0.035	4.43	6061-0	0.5774
	4.5	0.035	4.43	6061-T4	0.5774
	4.5	0.035	4.43	6061-T6	0.5774
	4.5	0.049	4.4	6061-T0	0.8058
	4.5	0.049	4.4	6061-T4	0.8058
	4.5	0.049	4.4	6061-T6	0.8058
	4.5	0.065	4.37	6061-T0	1.0650
	4.5	0.065	4.37	6061-T4	1.0650
	4.5	0.065	4.37	6061-T6	1.0650
	4.5	0.083	4.33	Pipe	1.3540
	4.5	0.120	4.26	6061-T6	1.9420
	4.5	0.120	4.26	6063-T1	1.9220

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>4 1/2"</b>	4.5	0.120	4.26	Pipe	1.9420
	4.5	0.125	4.25	6061-T6511	2.0200
	4.5	0.188	4.12	6061-T6511	2.9950
	4.5	0.237	4.03	Pipe	3.7330
	4.5	0.250	4	6061-T6511	3.9260
	4.5	0.337	3.83	Pipe	5.1830
	4.5	0.375	3.75	6061-T6511	5.7150
	4.5	0.500	3.5	2024-T3511	7.6150
	4.5	0.500	3.5	6061-T6511	7.3890
	4.5	0.500	3.5	7075-T6511	7.6150
	4.5	0.750	3	2024-T3511	10.7100
	4.5	0.750	3	6061-T6511	10.3900
	4.5	1.000	2.5	6061-T6511	12.9300
<b>4 3/4"</b>	4.75	0.375	4	6061-T6511	6.0610
	4.75	0.500	3.75	6061-T6511	7.8510
	4.75	0.750	3.25	2024-T3511	11.4200
<b>5"</b>	5	0.035	4.93	6061-0	0.6420
	5	0.035	4.93	6061-T4	0.6420
	5	0.035	4.93	6061-T6	0.6420
	5	0.042	4.92	6061-T0	0.7693
	5	0.049	4.9	6061-0	0.8963
	5	0.049	4.9	6061-T4	0.8963
	5	0.049	4.9	6061-T6	0.8963
	5	0.051	4.9	3004-H26	0.9420
	5	0.062	4.88	6061-T6	1.1310
	5	0.065	4.87	6061-T0	1.1850
	5	0.065	4.87	6061-T4	1.1850
	5	0.065	4.87	6061-T6	1.1850
	5	0.072	4.86	6063-T6	1.2970
	5	0.083	4.83	6061-T4	1.4920
	5	0.083	4.83	6063-T6	1.4920
	5	0.125	4.75	6061-T6511	2.2510
	5	0.188	4.62	6061-T6511	3.3420
	5	0.188	4.62	6063-T6	3.3080
	5	0.250	4.5	6061-T6511	4.3870
	5	0.313	4.37	6061-T6511	5.4200
	5	0.375	4.25	6061-T6511	6.4070

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>5"</b>	5	0.500	4	2024-T3511	8.5670
	5	0.500	4	6061-T6511	8.3130
	5	0.500	4	7075-T6511	8.5670
	5	0.625	3.75	2024-T3511	10.4100
	5	0.625	3.75	6061-T6511	10.1000
	5	0.750	3.5	2024-T3511	12.1400
	5	0.750	3.5	6061-T6511	11.7800
	5	0.750	3.5	7075-T6511	12.1400
	5	1.000	3	6061-T6511	14.7800
	5	1.125	2.75	6061-T6511	16.1100
<b>5 1/4"</b>	5.25	0.125	5	6063-T6	2.3430
	5.25	0.250	4.75	6061-T6511	4.6180
	5.25	0.500	4.25	6061-T6511	8.7750
	5.25	0.625	4	2024-T3511	11.0100
	5.25	0.750	3.75	6061-T6511	12.4700
	5.25	1.000	3.25	6061-T6511	15.7000
<b>5 1/2"</b>	5.5	0.035	5.43	6061-T6	0.7067
	5.5	0.042	5.42	6061-T4	0.8469
	5.5	0.049	5.4	6061-T4	0.9868
	5.5	0.062	5.38	6063-T6	1.2460
	5.5	0.125	5.25	6061-T6511	2.4820
	5.5	0.250	5	6061-T6	4.8490
	5.5	0.250	5	6061-T6511	4.8490
	5.5	0.250	5	6061-T6	4.8490
	5.5	0.375	4.75	6061-T6511	7.1010
	5.5	0.500	4.5	2024-T3511	9.5190
	5.5	0.500	4.5	6061-T6511	9.2360
	5.5	0.625	4.25	6061-T6511	11.2600
	5.5	0.750	4	2024-T3511	13.5600
	5.5	0.750	4	6061-T6511	13.1600
	5.5	0.750	4	7075-0	13.5600
	5.5	0.875	3.75	7075-T6	15.4100
	5.5	1.000	3.5	6061-T6511	16.6300
<b>6"</b>	6	0.049	5.9	6061-0	1.0770
	6	0.049	5.9	6061-T4	1.0770
	6	0.049	5.9	6061-T6	1.0770
	6	0.051	5.9	3004-H26	1.1320

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>6"</b>	6	0.051	5.9	5050 Irrigation	1.1090
	6	0.065	5.87	6061-T4	1.4250
	6	0.065	5.87	6063-T6	1.4250
	6	0.083	5.83	6063-T1	1.7960
	6	0.083	5.83	6063-T6	1.7960
	6	0.125	5.75	6061-T6511	2.7130
	6	0.125	5.75	6061-T6	2.7130
	6	0.125	5.75	6063-T1	2.6860
	6	0.125	5.75	6063-T6	2.6860
	6	0.140	5.72	6061-T6	3.3260
	6	0.188	5.62	6061-T6511	4.0370
	6	0.250	5.5	6061-T6511	5.3110
	6	0.375	5.25	6061-T6511	7.7930
	6	0.500	5	6061-T6511	10.1600
	6	0.750	4.5	2024-T3511	14.9900
	6	0.750	4.5	6061-T6511	14.5500
	6	1.000	4	2024-T3511	19.0400
	6	1.000	4	6061-T6511	18.4700
	6	1.250	3.5	6061-T6511	21.9400
<b>6 1/4"</b>	6.25	0.125	6	6061-T6	2.83
	6.25	0.125	6	6063-T832	2.8
	6.25	0.250	5.75	6061-T6511	5.54
	6.25	0.375	5.5	6061-T6511	8.14
	6.25	0.500	5.25	6061-T6511	10.62
<b>6 1/2"</b>	6.5	0.25	6	6061-T6511	5.7730
	6.5	0.38	5.75	6061-T6511	8.4860
	6.5	0.5	5.5	6061-T6511	11.0800
	6.5	0.63	5.25	2024-T3511	13.9800
	6.5	0.63	5.25	6061-T6511	13.5700
	6.5	0.75	5	6061-T6511	15.9300
	6.5	1	4.5	6061-T6511	20.3200
<b>6 5/8"</b>	6.63	0.11	6.41	Pipe	2.62
	6.63	0.13	6.36	Pipe	3.21
	6.63	0.28	6.07	Pipe	6.56
	6.63	0.43	5.76	Pipe	9.88
<b>6 3/4"</b>	6.75	0.5	5.75	6061-T6511	11.55
	6.75	0.75	5.25	6061-T6511	16.62

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
<b>7"</b>	7	0.05	6.9	6063-T6	1.2580
	7	0.06	6.88	6063-T6	1.4880
	7	0.08	6.84	6063-T6	1.9740
	7	0.08	6.83	6063-T6	3.1430
	7	0.13	6.75	6063-T6	2.0990
	7	0.25	6.5	6061-T6511	6.2350
	7	0.25	6.5	6063-T6	6.1710
	7	0.5	6	2024-T3511	12.3800
	7	0.5	6	6061-T6511	12.0100
	7	0.63	5.75	7075-T6511	15.1700
	7	0.69	5.62	7075-T6511	16.5400
	7	0.75	5.5	6061-T6511	17.3200
	7	1	5	6061-T6511	22.1700
	7	1.5	4	6061-T6511	30.4800
<b>7 1/2"</b>	7.5	0.08	7.34	6061-0	2.1390
	7.5	0.25	7	6061-T6511	6.6960
	7.5	0.38	6.75	6061-T6511	9.8720
	7.5	0.5	6.5	6061-T6511	12.9300
	7.5	0.63	6.25	6061-T6511	15.8800
	7.5	0.75	6	6061-T6511	18.7000
	7.5	1	5.5	6061-T6511	24.0100
<b>8"</b>	8	0.05	7.9	3004-H26	1.5130
	8	0.13	7.75	6061-T6511	3.6370
	8	0.13	7.75	6063-T6	3.6000
	8	0.25	7.5	5086-H32	7.0120
	8	0.38	7.25	6061-T6511	10.5600
	8	0.5	7	6061-T6511	13.8600
	8	0.75	6.5	6061-T6511	20.0900
	8	0.75	6.5	7075-T6511	20.7000
	8	1	6	2024-T3511	26.6500
	8	1	6	6061-T6511	25.8600
<b>8 1/4"</b>	8.25	0.13	8	6061-T6	3.75
<b>8 1/2"</b>	8.5	0.08	8.34	6061-0	2.43
	8.5	0.08	8.34	6061-T6	2.43
	8.5	0.5	7.5	6061-T6511	14.7
	8.5	0.75	7	6061-T6511	21.47
	8.5	1	6.5	6061-T6511	27.71

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
8 5/8"	8.63	0.25	8.13	Pipe	7.74
	8.63	0.32	7.98	Pipe	9.88
	8.63	0.5	7.63	Pipe	15.01
9"	9	0.25	8.5	6061-T6511	8.08
	9	0.5	8	6061-T6511	15.7
	9	0.75	7.5	6061-T6511	22.86
	9	1	7	6061-T6511	29.56
	9	2	5	6061-T6511	51.72
9 1/2"	9.5	0.75	8	6061-T6511	24.25
10"	10	0.05	9.9	3004-H26	1.89
	10	0.09	9.81	3004 Irrigation	3.44
	10	0.25	9.5	6061-T6511	9.01
	10	0.5	9	6061-T6511	17.55
	10	0.63	8.75	6061-T6511	21.65
	10	0.75	8.5	6061-T6511	25.63
	10	1	8	6061-T6511	33.25
10 1/4"	10.25	0.13	10	6061-T6	4.68
10 1/2"	10.5	0.5	9.5	6061-T6511	18.47
	10.5	1	8.5	6061-T6511	35.1
10 3/4"	10.75	1	8.75	6061-T6511	36.02
11"	11	0.38	10.25	6061-T6511	14.72
	11	0.5	10	6061-T6511	19.4000
	11	0.75	9.5	6061-T6511	28.4000
	11	1	9	6061-T6511	36.95
	11	2	7	6061-T6511	66.5
12"	12	0.25	11.5	6061-T6511	10.85
	12	0.5	11	6061-T6511	21.24
	12	0.75	10.5	6061-T6511	31.17
	12	1	10	6061-T6511	40.64
	12	2	8	6061-T6511	73.89
12 3/4"	12.75	0.5	11.75	6061-T6511	22.63
	12.75	1	10.75	6061-T6511	43.41

O.D. (fraction)	O.D. (decimal)	Wall	I.D.	Type	Wt/ft
--------------------	-------------------	------	------	------	-------

## Alcobra Metals, Inc.

*Distributor of Specialty Metals*

*“No order is too small!”*

4510 N Freya, Spokane, WA 99217

(509)482-4435 Fax(509)482-4512